State College Area High School State College, Pennsylvania



Bryce Burkentine

Penn State Architectural Engineering

Construction Management

Advisor Dr. Chimay Anumba

Spring 2016

Project Background

Presentation Outline



Project Background

Analysis 1: Design Of Interior Walls And

Analysis 2: Existing Roof Redesign

Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During

Construction While School Is In Session

Conclusions/Recommendations

Acknowledgments

Building Name | State College Area High School

Location | State College, Pennsylvania

Project Size | 650,000 square feet

Contract Value | \$115 Million Project Cap

Organizational Structure CM Agency W/ Multiple Prime

Contracts

Dates of Construction | October 2015 - Summer 2019









Plan for the Unexpected


Presentation Outline






Analysis 1: Design Of Interior Walls And Partitions

Inalysis 3: Interior Finishes Pods A-D SIPS



alysis 2: Existing Roof

Redesign




Analysis 4: Safety Provisions

During Construction While

School Is In Session








nalysis 1: Design Of Interior Walls And
Partitions

Analysis 2: Existing Roof
Redesign




Analysis 3: Interior Finishes Pods A-D SIPS



Analysis 4: Safety Provisi During Construction Whi

School Is In Session







Analysis 1: Design Of Interior Walls And

Analysis 3: Interior Finishes Pods A-D SIPS


Analysis 4: Safety Provisions During


Construction While School Is In Session





Analysis 3: Interior Finishes Pods A-D SIPS







Analysis 1: Design Of Interior Walls And


Analysis 2: Existing Roof Redesign


Analysis 3: Interior Finishes Pods A-D SIPS


Analysis 4: Safety Provisions During

Construction While School Is In Session

Conclusions/Recommendations







Analysis 4: Safety Provisions During Construction While School Is In Session



Design of Interior Walls and Partitions

Presentation Outline



CMU Walls

Structural Metal Stud Walls

- Great Durability
- Good Acoustical Performance
- Poor Thermal Performance
- "Wet Construction" Needs time to dry in lifts = timely to Construct
- Weather Restraints Cold/Wet

- Fast to Construct
- Poor Acoustical Performance

Cost Sensitive



Structural Metal Stud Wall System Cost

Metal Studs 12"O.C. w/ Channels	\$1,798,600.00
Fasteners	\$9,030.00
Assembly screws	\$9,000.00
Bracing	\$506,000.00

\$2,322,630.00





\$ 6.84 Cost Difference

Presentation Outline



Analysis 1: Design Of Interior Walls And Partitions

Background/Goals

Cost Analysis

Schedule Analysis

Acoustical Breadth

Conclusions

Analysis 2: Existing Roof Redesign

Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During Construction

While School Is In Session

Conclusions/Recommendations

Acknowledgments

Design of Interior Walls and Partitions



	Calculated Durations For Metal Stud Walls								
Building Section	Unit	Take-off	Men per Crew	Daily Crew Output		Total Manpower men/crew x # of crews	Output Per Hour daily output/8hr		Duration (Days) # hours/8
Α	LF	5000	2	34	3	6	4	392.16	49.02
В	LF	5600	2	34	3	6	4	439.22	54.90
С	LF	5600	2	34	3	6	4	439.22	54.90
D	LF	5600	2	34	3	6	4	439.22	54.90
E1	LF	3100	2	34	3	6	4	243.14	30.39
E2	LF	3700	2	34	3	6	4	290.20	36.27
F1	LF	1500	2	34	3	6	4	117.65	14.71
F2	LF	4300	2	34	3	6	4	337.25	42.16
G1	LF	3900	2	34	3	6	4	305.88	38.24
G2	LF	3000	2	34	3	6	4	235.29	29.41
							Tota	al	404.90

	Calculated Durations For Drywall Durations									
ilding ction	Unit	Take-off	Men per Crew	Daily Crew Output		man/craw v # atl	Output Per Hour	Crawc v	Duration (Days) # hours/8	
Α	SF	46000	2	675	5	10	84	109.04	13.63	
В	SF	44500	2	675	5	10	84	105.48	13.19	
С	SF	44500	2	675	5	10	84	105.48	13.19	
D	SF	44500	2	675	5	10	84	105.48	13.19	
E1	SF	24000	2	675	5	10	84	56.89	7.11	
E2	SF	24000	2	675	5	10	84	56.89	7.11	
F1	SF	9000	2	675	5	10	84	21.33	2.67	
F2	SF	41000	2	675	5	10	84	97.19	12.15	
G1	SF	34500	2	675	5	10	84	81.78	10.22	
G2	SF	24500	2	675	5	10	84	58.07	7.26	
							Tota	al	99.70	

Project Background

Analysis 1: Design Of Interior Walls And Partitions

Background/Goals

Cost Analysis

Schedule Analysis

Acoustical Breadth

Conclusions

Analysis 2: Existing Roof Redesign

Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During Construction

While School Is In Session

Conclusions/Recommendations

Acknowledgments

Direct Structural Wall Schedule Comparison							
Type Duration Percent Schedule Differen							
CMU	455						
Structural Metal Studs	354	22.2%	101 Days				

Project Background

Analysis 1: Design Of Interior Walls And Partitions

Background/Goals

Cost Analysis

Schedule Analysis

Acoustical Breadth

Conclusions

Analysis 2: Existing Roof Redesign

Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During Construction

While School Is In Session

Conclusions/Recommendations

Acknowledgments

Overall Schedule Comparison							
Туре	Duration	Percent	Schedule Difference				
CMU	455		76 Days				
Structural Metal Studs	379	16.7%					


Original Schedule: 455 Days

Direct Structural Savings: - 101 Days

Drywall addition: + 25 Days

New Schedule Duration: 379 Days

Presentation Outline



Sound Transfer Differences Between CMU Walls and Structural Metal Stud Walls

Bryce Burkentine Construction Management Option

American National Standard Acoustical Performance Criteria

Table B.1 — Minimum STC ratings recommended between an ancillary space and an adjacent space

		Adjacer	nt space	
Receiving ancillary learning space	Corridor or staircase a), common-use, and public-use toilet and bathing room b)	Music room	Office or conference room a)	Mechanical equipment room ^{f)} , cafeteria, gymnasium, or indoor swimming pool
Corridor used as ancillary learning space	45	60°)	45 ^{d)}	55 ^{c)}
Music room	45	60	60 ^{e)}	60
Office or conference room	45 ^{d)}	60 ^{g)}	45 ^{d)}	60

- a) For corridor, staircase, office or conference room walls containing entrance doors to the ancillary learning space, the STC rating of the basic wall, exclusive of the door, should be 45. The entrance door should conform to the requirements of 5.4.2.4.
- b) The STC rating for an ancillary space/toilet partition does not apply when the toilet is private and connected to a private office. An STC rating greater than 45 may be required for separating a quiet office or conference room from a common-use or public-use toilet or bathing room.
- c) When the corridor will not be used as an ancillary learning space, the minimum STC rating may be reduced to not less than 45. Use of corridors as ancillary learning spaces should be avoided when they are located next to the noisy spaces indicated in the table by the high STC ratings.
- d) When acoustical privacy is needed for conversations in an office or conference room, the minimum rating should be a composite STC of 50 instead of 45 that includes the effects of any doors or windows etc.
- e) An STC rating of 60 is justified to prevent the music space from interfering with hearing in the office or conference room.
- f) Isolation between ancillary learning spaces and mechanical equipment rooms is dependent on the noise level in the mechanical equipment room and can be less than STC 60 in some cases but should never be less than STC 45.
- g) The STC rating of 60 does not apply when the office is for the music teacher and opens to the music room.

Project Background

Analysis 1: Design Of Interior Walls And Partitions

Background/Goals

Cost Analysis

Schedule Analysis

Acoustical Breadth

Conclusions

Analysis 2: Existing Roof Redesign


Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During Construction


While School Is In Session

Conclusions/Recommendations

Acknowledgments



CMU Wall System



Structural Metal Stud Wall System





Analysis 1: Design Of Interior Walls And Partitions

Background/Goals

Cost Analysis

Schedule Analysis

Acoustical Breadth

Conclusions

Analysis 2: Existing Roof Redesign

Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During Construction

While School Is In Session

Conclusions/Recommendations

Acknowledgments

CMU Wall System

8" CMU Wall

	44]		
		•		
1/3 tave- and quency	Contour Level	ΤL	Deficiency	Max Deficiency ≤ 8 dB?
Hz)	(dB)	(dB)	(dB)	
125	28	32	0	OK
160	31	32	0	OK
200	34	32	2	OK
250	37	36	1	OK
315	40	38	2	OK
100	43	40	3	OK
i00	44	42	2	OK
30	45	43	2	OK
300	46	45	1	OK
000	47	47	0	OK
250	48	44	4	OK
600	48	43	5	OK
000	48	47	1	OK
500	48	47	1	OK
150	48	49	0	OK
000	48	50	0	ОК
		TOTAL	24	0
	Wal	II is STC:	44	

12" CMU Wall

STC	39								
		-							
1/3 Octave- Band Frequency	Contour Level	TL	Deficiency	Max Deficiency s 8 dB?					
(Hz)	(dB)	(dB)	(dB)						
125	23	29	0	ОК					
160	26	30	0	ОК					
200	29	31	0	ОК					
250	32	31	1	ОК					
315	35	34	1	ОК					
400	38	34	4	ОК					
500	39	35	4	ОК					
630	40	35	5	ОК					
800	41	33	80	OK					
1000	42	35	7	ОК					
1250	43	41	2	ОК					
1600	43	45	0	ОК					
2000	43	48	0	ОК					
2500	43	50	0	ОК					
3150	43	52	0	ОК					
4000	43	54	0	ОК					
		TOTAL	32	0					
	'								
	Wall is STC: 39								

Structural Metal Stud Wall System

	60			
1/3 tave- and quency	Contour Level	TL	Deficiency	Max Deficiency s 8 dB?
Hz)	(dB)	(dB)	(dB)	
125	44	40	4	ОК
160	47	47	0	OK
200	50	51	0	OK
250	53	55	0	ОК
315	56	57	0	OK
100	59	60	0	ОК
500	60	62	0	OK
530	61	63	0	ОК
300	62	64	0	OK
000	63	64	0	OK
250	64	65	0	ОК
600	64	64	0	OK
000	64	58	6	ОК
500	64	58	6	OK
150	64	62	2	ОК
000	64	66	0	ОК
		TOTAL	18	0
	'			
	Wal	l is STC:	60	



Analysis 1: Design Of Interior Walls And Partitions

Background/Goals

Cost Analysis

Schedule Analysis

Acoustical Breadth

Conclusions

Analysis 2: Existing Roof Redesign

Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During Construction


While School Is In Session

Conclusions/Recommendations


Acknowledgments

CMU Wall System

8" CMU Wall



12" CMU Wall



Structural Metal Stud Wall System





Analysis 1: Design Of Interior Walls And Partitions

Background/Goals

Cost Analysis

Schedule Analysis

Acoustical Breadth

Conclusions

Analysis 2: Existing Roof Redesign

Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During Construction

While School Is In Session


Conclusions/Recommendations


Acknowledgments





Cost and Schedule Savings







Project Background

Analysis 1: Design Of Interior Walls And Partitions

Analysis 2: Existing Roof Redesign

Background/Goals

Cost Analysis

Schedule Analysis

Structural Breadth

Conclusions

Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During Construction

While School Is In Session


Conclusions/Recommendations

Acknowledgments

F2 Redesign of Existing Roof Cost Breakdown													
Item	Amount	Unit	Material Cost		Material Total	Lal	oor Cost	L	Labor Total	uipmen Costs	Ec	quipment Total	Γotal Cost
emolition													
ixture of Types	50700	CF	\$ -	\$	-	\$	0.14	\$	7,098.00	\$ 0.17	\$	8,619.00	\$ 15,717.00
ists													
K1 Series	28	Ton	\$ 1,625.00	\$	45,500.00	\$	248.00	\$	6,944.00	\$ 107.00	\$	2,996.00	\$ 55,440.00
oof Decking													
ga- 50-500 squares	38000	SF	\$ 1.94	\$	73,720.00	\$	0.31	\$	11,780.00	\$ 0.04	\$	1,520.00	\$ 87,020.00
sulation													
perboard high density, 1/2" Thick	38000	SF	\$ 0.30	\$	11,400.00	\$	0.20	\$	7,600.00	\$ -	\$	-	\$ 19,000.00
oofing													
odified Bituminous Membrane	38000	SF	\$ 3.30	\$	125,400.00	\$	3.50	\$	133,000.00	\$ 1.96	\$	74,480.00	\$ 332,880.00
										Т	ota	l	\$ 510,057.00



Presentation Outline




Existing Roof Redesign

	F2- Calculated Durations For Roof Redesign								
Activity	Unit	Take-off	Men per Crew	Daily Crew Output	Number of Crews	Total Manpower men/crew x # of crews	Output Per Hour daily output/8hr	Duration (Hrs) takeoff/(# of crews x output per hour)	, , ,
emolition	CY	50700	18	5750	1	18	719	70.54	8.82
Joists	Ton	28	13	15	1	13	2	14.93	1.87
of Decking	SF	38000	5	4147	1	5	518	73.31	9.16
sulation	SF	38000	2	2600	1	2	325	116.92	14.62
Roofing	SF	38000	2	2400	1	2	300	126.67	15.83
							Tot	·al	E0 20


	Bryce Burkentine
Construction	Management Option

							_					
ID		I .	Task Name	2uration	Start	Finish	Predecessors	March	April	May	June	July
	U	Mode						2/26 3/5 3/12 3/19	3/26 4/2 4/9 4/1	6 4/23 4/30 5/7 5/1	14 5/21 5/28 6/4 6/1	1 6/18 6/25 7/2 7/9 7
1		*	Demolition	3 days	Wed 3/1/17	Fri 3/3/17						
2		A .	Slab on Grade	10 days	Mich 3/6/17	Fri 3/17/17	1					
3		*	Install Structural Metal Studs	43 days	Tue 3/14/17	Thu 5/11/17	2SS+6 days	<u> </u>		3 7		1
4		*	Joists	2 days	Fri 5/12/17	Mon 5/15/17	3			žs,		
5		AP.	Roof Decking	10 days	Tue 5/16/17	Mon 5/29/17	4			Æ		1
6		*	Insulation	15 days	Thu 5/25/17	Wed 6/14/17	5SS+7 days					
7		A .	Roofing	16 days	Tue 6/6/17	Tue 6/27/17	bSS+8 days				-	



G2

Presentation Outline



В **E2** G1



Determining New Size Joists due to Additional Snow Loads

Presentation Outline

Project Background

Analysis 1: Design Of Interior Walls And Partitions

Analysis 2: Existing Roof Redesign

Background/Goals

Cost Analysis

Schedule Analysis

Structural Breadth

Conclusions


Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During Construction

While School Is In Session

Conclusions/Recommendations

Acknowledgments



Dead Load:

- Metal Deck 2psf
- •Roofing 2psf
- Rigid Insulation 2psf
- •MISC Dead Load 10psf

Dead Total = 16psf

$$W_T = (1.2D + 1.6L) \times T_w$$


684.8plf=((1.2x16psf)+(1.6x95psf)) x 4ft

$$W_{LL} = (L) \times T_w$$

380plf=(95psf) x 4ft

825plf>684.8plf 510plf>380plf

Concludes Joists are 12K1



Project Background

Analysis 1: Design Of Interior Walls And Partitions

Analysis 2: Existing Roof Redesign

Background/Goals

Cost Analysis

Conclusions

Schedule Analysis

Structural Breadth


Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During Construction

While School Is In Session

Conclusions/Recommendations


Acknowledgments




Cost would increase due to demoing existing roof and constructing a new roof

In a few months budget will be known and the board can make an educated decision

Presentation Outline




Interior Finishes Pods A-D SIPS



Bryce Burkentine Construction Management Option

	Production Rates	
ID	Interior Buildout	Total Manpower
1	Hang Drywall	2
2	Spackle/Finish Drywall	2
3	Install Finish Carpentry and Prehung Doors	2
4	Prep/Prime	2
5	Paint Walls	3
6	Install Flooring	2
7	Install Casework	2
8	Install Grids in Ceiling	4
9	MEP Finals	6
10	Install Ceiling Tiles	2
11	Install Door Hardware,Visual Display Units, Lockers	6
12	Final Finish Casework	2
13	Install Carpet	2
14	Final Touch-Ups	2
15	Final Cleaning	2

Presentation Outline



Interior Finishes Pods A-D SIPS

	Calculated Durations For Ceiling Grid Installers Pods C & D Total Tota														
uilding	Floor	Zone	Unit	Take-off	Men per Crew	Daily Crew Output	Number of Crews	Total Manpower men/crew x # of crews	Output Per Hour daily output/8hr	Duration (Hrs) takeoff/(# of crews x output per hour)	Duration (Days) # hours/8				
Pod C	1	1	SF	6836	1	475	4	4	59	28.78	3.60				
Pod C	1	2	SF	6850	1	475	4	4	59	28.84	3.61				
Pod C	1	3	SF	6869	1	475	4	4	59	28.92	3.62				
Pod D	1	1	SF	6836	1	475	4	4	59	28.78	3.60				
Pod D	1	2	SF	6850	1	475	4	4	59	28.84	3.61				
Pod D	1	3	SF	6869	1	475	4	4	59	28.92	3.62				
Pod C	2	1	SF	6836	1	475	4	4	59	28.78	3.60				
Pod C	2	2	SF	6850	1	475	4	4	59	28.84	3.61				
Pod C	2	3	SF	6869	1	475	4	4	59	28.92	3.62				
Pod D	2	1	SF	6836	1	475	4	4	59	28.78	3.60				
Pod D	2	2	SF	6850	1	475	4	4	59	28.84	3.61				
Pod D	2	3	SF	6869	1	475	4	4	59	28.92	3.62				
Pod C	3	1	SF	6836	1	475	4	4	59	28.78	3.60				
Pod C	3	2	SF	6850	1	475	4	4	59	28.84	3.61				
Pod C	3	3	SF	6869	1	475	4	4	59	28.92	3.62				
Pod D	3	1	SF	6836	1	475	4	4	59	28.78	3.60				
Pod D	3	2	SF	6850	1	475	4	4	59	28.84	3.61				
Pod D	3	3	SF	6869	1	475	4	4	59	28.92	3.62				

	Bryce Burkentine
nstruction	Management Option

	Calculated Durations For Painters Pods C & D													
Building	Floor	Zone	Unit	Take-off LF of walls x height	Men per Crew	Daily Crew Output	Number of Crews	Total Manpower men/crew x # of crews	Output Per Hour daily output/8hr	Duration (Hrs) takeoff/(# of crews x output per hour)	Duration (Days) # hours/8			
Pod C	1	1	SF	9187.5	1	2275	3	3	284	10.77	1.35			
Pod C	1	2	SF	12075	1	2275	3	3	284	14.15	1.77			
Pod C	1	3	SF	7612.5	1	2275	2	2	284	13.38	1.67			
Pod D	1	1	SF	9187.5	1	2275	3	3	284	10.77	1.35			
Pod D	1	2	SF	12075	1	2275	3	3	284	14.15	1.77			
Pod D	1	3	SF	7612.5	1	2275	2	2	284	13.38	1.67			
Pod C	2	1	SF	9187.5	1	2275	3	3	284	10.77	1.35			
Pod C	2	2	SF	12075	1	2275	3	3	284	14.15	1.77			
Pod C	2	3	SF	7612.5	1	2275	2	2	284	13.38	1.67			
Pod D	2	1	SF	9187.5	1	2275	3	3	284	10.77	1.35			
Pod D	2	2	SF	12075	1	2275	3	3	284	14.15	1.77			
Pod D	2	3	SF	7612.5	1	2275	2	2	284	13.38	1.67			
Pod C	3	1	SF	9187.5	1	2275	3	3	284	10.77	1.35			
Pod C	3	2	SF	12075	1	2275	3	3	284	14.15	1.77			
Pod C	3	3	SF	7612.5	1	2275	2	2	284	13.38	1.67			
Pod D	3	1	SF	9187.5	1	2275	3	3	284	10.77	1.35			
Pod D	3	2	SF	12075	1	2275	3	3	284	14.15	1.77			
Pod D	3	3	SF	7612.5	1	2275	2	2	284	13.38	1.67			

Project Background

Analysis 1: Design Of Interior Walls And Partitions

Analysis 2: Existing Roof Redesign

Analysis 3: Interior Finishes Pods A-D SIPS

Background/Goals
Interior Trade Selection/Manpower

SIP Schedule
Conclusions

Analysis 4: Safety Provisions During Construction


While School Is In Session


Conclusions/Recommendations

Acknowledgments


	Interior Finishes SIPS- State College Area High School Pods C-D																																													
							J	lul	у									A	۱ug	ust								Se	pte	emk	er									00	tel	or				
ıildi ng	Floor	Zone	We	ek	1 1	Ne				ek	3 \	We	ek 4	4 W	/ee	k 5	W		Ī			7 \	Vee	k 8	W	eek	9	We	ek	W	/ee			eek 12		We	eek 3	I		eek .4	T'	We 1!		V	Veel 16	k
			12	3 4	5 1	2	3 4	5 :	12	3 4	5 1	123	3 4 !	5 1	2 3	45	1 2	234	45	12	3 4	5 1	23	45	2	3 4	5 1					45			5 1			5 1			5 1			5 1 2	2 3 4	15
d C	1	1	1	2	3	4	5		5	6	7	8	9			1 1																														
d C	1	2		1	2	3	4	ı I	5	5	6	7	8	9	1	0 1	1 1	12	13	14	15																\prod	T	\prod	П				\prod		\prod
d C	1	3			1	2	3	3	4	5	5	6	7	8	g	1	0 1	11	12	13	14	15																								
d D	1	1				1	2	2	3	4	5	5	6	7	8	3 9) 1	10	11	12	13	14	15														\prod	T	\prod	\prod				П		П
d D	1	2					1	L	2	3	4	5	5	6	7	7 8	3	9	10	11	12	13	14	15																						П
d D	1	3				П			1	2	3	4	5	5	6	5 7	7	8	9	10	11	12	13	14	15							П					П	T	\prod	П				П		П
	2	1								1	2	3	4	5	-	5 6	5	7	8	9	10	11	12	13	14	15												T		\Box	T					П
d C	2	2		-							1	2	3	4		5 5	5	6	7	8	9	10	11	12	13	14	15					П					П	T	П	П				П		П
d C	2	3										1	2	3			_	5	6	7	8	9	10	11	12	13	14	15				T						T	П	\Box		П		Ħ		П
d D	2	1				П							1	2	F			5	5	6	7	8	9	10	11	12	13	14	15			П					П	T	П	П	\top	П		П	\top	П
d D	2	2				П							П	1	2	3	3	4	5	5	6	7	0			11		13	14	15		П						\top	\top	\top					#	П
d D	2	3		\dagger		$\dagger\dagger$	$\dagger \dagger$		\parallel		\dagger		$\dagger \dagger$		1		2	3	4	5	5	6	7	8				12		14		5			\top	$\dagger\dagger$	$\dagger\dagger$	†	$\dagger \dagger$	$\forall \uparrow$	†	T	$\dagger \dagger$	$\dagger \dagger$	#	\forall
d C	3	1		\dagger		$\dagger \dagger$	\parallel		\parallel		\dagger		$\dagger \dagger$	$\dagger \dagger$		1	L	2	3	4	5	5	6	7	8	9	_	11					5				∄	\top	$\dagger \dagger$	\forall	†	\dagger		$\dagger \dagger$	$\dagger \dagger$	П
d C	3	2				Ħ			П				$\dagger \dagger$					1	2	3	4	5	5	6	7	8	9	_		12				' 			\prod		十	#				Ħ	$\dagger \dagger$	П
d C	3	3		\dagger	T	$\dagger \dagger$	\parallel		\parallel		H	$\dagger \dagger$	$\dagger \dagger$	\forall					1	2	3	4	5	5	6	7	8						_	4 1	5	$\dagger\dagger$	$\dagger \dagger$	+	+	$\forall t$	+	П			+	Ħ
d D	3	1				$\dagger\dagger$	\parallel	1	\dagger		\parallel	$\dagger \dagger$	$\dagger \dagger$	\forall				T	Ī	1	2	3	4	5	5	6	7	8	9	10				3 1		15	$\dagger\dagger$	+	$\dagger \dagger$	\forall	+	\forall	T	$\dagger\dagger$	+	\forall
d D	3	2		\dagger		$\dagger\dagger$	+		\dagger		\dagger		$\dagger\dagger$	+		+		$\dagger \dagger$	\dagger	Ť	1	2	3	4	5	5	6	7	8	9	_			2 1	_		15	$^{+}$	+	+	+	\vdash	T	$\dagger\dagger$	+	\forall
d D	3	3				$\dagger\dagger$	+		\parallel		H		$\dagger \dagger$					$\dagger \dagger$	+		_	1	2	3	Δ	5	5	6	7	8			0 1			13		15	+	++	+	\vdash	+	$\dagger\dagger$	++	\forall

									Ju	ly									Aug	gust				
di	Floor	Zone	V	Ve	ek 1 Week 2				W	eek	3	Wee	k 4	We	eek	5 \	Vee	k 6	We	eek	7	We	ek 8	
5			1	2	3 4	5	1	2 3	4 5	12	3 4	5 2	1 2 3	45	12	3 4	5 1	23	45	1 2	3 4	5 2	1 2	3 4 5
С	1	1	1	L	2	3		4	5	5	6	7	8	9	10	11	12	13	14	15				
С	1	2			1	2		3	4	5	5	6	7	8	9	10	11	12	13	14	15			
С	1	3				1		2	3	4	5	5	6	7	8	9	10	11	12	13	14	15	,	
D	1	1						1	2	3	4	5	5	6	7	8	9	10	11	12	13	14	15	,
D	1	2							1	2	3	4	5	5	6	7	8	9	10	11	12	13	14	15
D	1	3								1	2	3	4	5	5	6	7	8	9	10	11	12	13	14





Original: 38 Weeks SIPS: 29 Weeks



Research Questions

- 1. What are the safety provisions set forth in the building codes and regulations for educational projects?
- 2. What are the practical safety provisions implemented by the industry and educational facility?
- 3. What are the available safety trainings, which workers and students are exposed to?



Background/Goals/Research Questions

Results/Discussion

Conclusions

Conclusions/Recommendations

Acknowledgments

Research Questions

- 1. What are the safety provisions set forth in the building codes and regulations for educational projects?
- 2. What are the practical safety provisions implemented by the industry and educational facility?
- 3. What are the available safety trainings, which workers and students are exposed to?

Why so Important:

- Sexual Predators Around Children
 - Students Health
 - Curious Students
- Noise Control While Students Are In The Classroom
 - Proper Ventilation
- Students Are Still In The Developing Stage

Project Background

Analysis 1: Design Of Interior Walls And Partitions

Analysis 2: Existing Roof Redesign

Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During Construction
While School Is In Session

Background/Goals/Research Questions Results/Discussion

Conclusions

Conclusions/Recommendations

Acknowledgments

Exposures

- Trip hazards
- Security Hazards
- Noise Control
- Proper Ventilation
- Falling Objects
- Etc...

Reactive Protocols

- Public School Code
- Occupational Safety and Health Administration (OSHA)
- Environmental Protection Agency (EPA)
- Pennsylvania Building Code
- Massaro Construction Management Services


Subset Acts & Regulations

- Pennsylvania State Police Criminal History Record
- Department of Public Welfare Child Abuse Report Federal History Record
- Information

 General Safety and Health
- ProvisionsThe Asbestos Hazard Emergency Response Act
- Centre County Refuse Requirements
- Safety Trainings from 3D Site Tour




Full Time Safety
Manager




CCELNG Sepa WOOL INCLIDENT COMMITTION C

Analysis 1: Design Of Interior Walls And
Partitions

Analysis 3: Interior Finishes Pods A-D SIPS



Analysis 2: Existing Roof
Redesign



Analysis 4: Safety Provisions

During Construction While

School Is In Session



Academic Acknowledgements

Dr. Chimay Anumba- Faculty Advisor

Dr. Michelle Vigeant

Dr. Ryan Solnosky

Dr. Robert Leicht

Architectural Engineering Department

Industry Acknowledgements





Special Thanks To

Tim Jones- Massaro CM Services

Ryan Cole- Massaro CM Services

Edward Poprik- State College High School

Facility Director

PACE Industry Members

My Family and Friends



QUESTIONS?



Presentation Outline



Project Background

Analysis 1: Design Of Interior Walls And

Partitions

Analysis 2: Existing Roof Redesign

Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During

Construction While School Is In Session

Conclusions/Recommendations

Acknowledgments

Design of Interior Walls and Partitions

Structural Metal Stud Wall System Cost														
ltem	Length	Number	Unit	Material Cost	Material Total	Labor Cost	Labor Total	Total Cost						
tal Studs 12"O.C. w/ Channels														
GA .	39100		LF	\$ 24.00	\$ 938,400.00	\$ 22.00	\$ 860,200.00	\$1,798,600.00						
teners														
teners		105	Вх	\$ 64.00	\$ 6,720.00	\$ 22.00	\$ 2,310.00	\$ 9,030.00						
embly screws														
embly screws		200	Ea	\$ 23.00	\$ 4,600.00	\$ 22.00	\$ 4,400.00	\$ 9,000.00						
cing														
tal Stud Bracing	11500		LF	\$ 22.00	\$ 253,000.00	\$ 22.00	\$ 253,000.00	\$ 506,000.00						
							Total	\$2,322,630.00						

Bryce Burkentine Construction Management Option

439.22 439.22 439.22

117.65 337.25

235.29

109.04

105.48 105.48 105.48

56.89

56.89

21.33 97.19

81.78

58.07

Total

Total

10

10

10

Α	LF	5000	2	34	3
В	LF	5600	2	34	3
С	LF	5600	2	34	3
D	LF	5600	2	34	3
E1	LF	3100	2	34	3
E2	LF	3700	2	34	3
F1	LF	1500	2	34	3
F2	LF	4300	2	34	3
G1	LF	3900	2	34	3
G2	LF	3000	2	34	3
	·		·	Calculated Du	rations For Drywa
Building Section	Unit	Take-off	Men per Cre	w Daily Crew Outpu	ut Number of Cre

46000

44500

44500

24000

24000

34500

24500

Take-off | Men per Crew | Daily Crew Output | Number of Crews

675

675

675

Calculated Durations For Metal Stud Walls

Presentation Outline



Project Background

Analysis 1: Design Of Interior Walls And

Partitions

Analysis 2: Existing Roof Redesign

Analysis 3: Interior Finishes Pods A-D SIPS

Analysis 4: Safety Provisions During

Construction While School Is In Session

Conclusions/Recommendations

Acknowledgments

Sound Transfer Differences Between CMU Walls and Structural Metal Stud Walls

APPENDIX J

Sound Transmission Loss Data

Assembly/Frequency (Hz)		STC	100	125	160	200	250
al stud, gypsum board (GB) assemblies with or withou	ut miner	al wool	or fiber	glass (F	G) insu	lation	
g. studs							
GB each side of 2-1/2" studs 24" o.c., 1.5" FG		45	19	22	26	31	38
e as above plus an additional layer GB on one side (2+1 layers)		50	22	31	31	38	43
e as above with two layers GB on each side (2+2 layers)		53	28	35	35	41	48
GB on each side of 2-1/2" studs 24" o.c., no insulation		39	22	24	24	28	37
e as above plus 1-1/2" FG		46	17	26	28	37	42
e as above, but with two layers GB on each side (2+2 layers)		54	30	37	37	41	46
GB on each side of 3-5/8" studs 16" o.c., no insulation	E	43	19	26	23	29	36
e as above but with 3" FG	6 0	49	20	28	30	37	43
layers 1/2" GB each side of 3-5/8" studs 24" o.c. plus 1-1/2" FG	G	55	31	34	36	46	47
GB each side of 3-5/8" studs 24" o.c. plus 1-1/2" FG	0	45	22	29	31	39	41
e as above but with 3" FG	C	49	18	32	33	39	44
GB (2+1 layers) on 3-5/8" studs 24" o.c. and 2" FG	9	51	28	36	37	42	46
e as above except 3" FG		53	25	35	41	46	51
GB (2+2 layers) on 3-5/8" studs 24" o.c., no insulation		48	27	34	30	37	41
GB (2+2 layers) on 3-5/8" studs 24" o.c., 3" FG	-	57	28	38	44	47	52
as above except 3+3 GB layers, a total of 6 GB layers	57	61	33	40	47	51	55
g. studs							
GB on each side of 3-5/8" studs, no insulation		39	16	26	19	26	36
as above plus 2" FG		41	19	30	29	34	43


300	400	500	630	800	1,000	1,250	1,600	2,000	2,500	3,150	4,000
		# #	11.00	7//25	122				45	43	46
44	48	51	53	55	57	58	58	54			
48	51	53	54	56	58	57	59	54	47	47	50
52	54	55	55	57	59	58	60	56	50	. 51	54
34	41	44	45	47	49	50	44	36	35	40	41
47	51	53	54	56	58	58	57	44	42	46.	48
50	53	55	55	59	60	58	56	51	51	54	58
36	42	43	47	48	51	54	53	48	42	40	43
43	49	51	54	55	58	60	60	55	48	46	50
51	55	56	56	60	61	60	63	59	52	54	57
43	49	51	53	55	56	57	55	43	41	46	48
45	48	51	55	57	58	58	57	55	45	46	53
50	52	54	55	59	59	58	58	47	47	51	53
54	56	59	58	58	58	60	60	55	49	54	59
42	48	51	52	53	54	55	56	46	45	48	52
55	58	59	59	60	60	62	61	56	53	58	62
57	60	62	63	64	64	65	64	58	58	62	66
35	40	41	43	45	47	50	48	38	36	40	42
44	44	46	48	51	52	52	48	37	38	42	44

	Bryce Buri	kentine
onstruction	Management	Option


Appendix		
	Sound Transmission Loss Data	

					2.00						1000		tm/helsiilli					CONTRACT.
low (8") lightweight concrete block masonry																		
c. block — plain	44	30	32	32	32	36	38	40	42	43	45	47	44	43	47	47	49	50
e as above, but 2 coats of paint or block filler both sides	48	38	38	36	36	38	42	44	45	47	48	50	51	52	52	51	52	55
c. block plus 1/2" plaster both sides	51	36	36	35	39	41	42	44	48	50	52	54	55	57	60	62	60	60
c. block, 5/8" GB on 1-1/2" furring, 1-1/2" FG bet. furring	55	29	37	42	49	48	47	49	50	52	55	57	60	62	61	58	61	66
e as above but GB on resilient channels	58	33	35	39	43	47	50	55	56	59	60	60	62	62	62	62	62	64
e as above but paint block on side opposite GB	60	38	41	43	47	49	52	57	58	58	63	66	68	70	69	68	69	72
c. block, 5/8" GB on 3" Z-channels	58	30	34	38	41	46	52	56	58	60	62	62	64	65	65	62	65	70
e as above but with 3" FG between Z-channels	61	35	42	44	48	49	56	58	59	60	62	62	64	65	65	62	66	72
c. block, 2-1/2" metal studs plus 5/8" GB both sides of block, but 2" PG in one stud cavity	65	32	41	47	55	60	69	73	74	74	75	73	72	72	73	71	75	78
e as above, but FG in both stud cavities	72	40	49	54	62	67	73	73	75	74	76	74	73	73	73	72	77	80
c. block, 2-1/2" metal studs plus 5/8" GB with 2-1/2" FG on one side, 3" Z-channels and 5/8" GB on other side	68	35	44	48	55	62	70	72	74	76	77	76	74	73	71	69	74	78
					18	175	•											
llow (6") lightweight concrete block masonry							37	38	40	43	45	47	48	51	55	55	53	54
c. block — plain	44	29	29	30	31	33	38	40	43	46	49	52	54	55	58	62	64	65
ne as above but with 2 coats of paint or block filler	48	36	38	39	36	34	41	43	48	52	55	57	57	58	61	64	63	60
c. block, 1/2" GB on 3/4" furring strips	49	30	31	30	33	35	44	45	49	52	54	56	56	60	63	61	58	61
ne as above but with 3/4" FG in cavity between furring strips	- 50	28	28	31	36	37	45	49	51	53	57	60	63	64	66	66	64	67
ic. block, 1/2" GB on 1-1/2" furring strips and 1-1/2" FG in cavity	55	31	38	45	45	42	52	56	58	60	63	65	66	66	67	69	73	76
ac. block, 2-1/2" metal studs plus 5/8" GB with 2-1/2" FG	61	39	44	46	47	48												
llow (12") lightweight concrete block masonry							34	34	35	35	33	35	41	45	48	50	52	54
nc. block — plain	39	26	29	30	31	31	43	44	45	48	50	51	54	56	57	56	58	60
ne as above but with 3 coats of paint or block filler to one side	51	28	35	35	40	43	49	52	55	59	62	66	69	72	72	69	68	70-
ne as above but add resilient channels and 1/2" GB on one side	57	31	37	37	41	46												

Presentation Outline



Determining New Size Joists due to Additional Snow Loads



Bryce Burkentine Construction Management Option

